



The Original Fitness Floor but thicker at a full 18mm thick.



**Say Hello to “Rolled Rubber
Three Quarter”**

We took the 9mm Classic,
and made it thicker - with a
total single layer thickness of
18mm. No wear layer = no
problem.


STRENGTH FROM WITHIN.

Scan QR code to view our catalog.

**ORDER
NOW**

www.PMXSTRENGTH.com

**5310 Ashbrook Drive
Houston, TX 77081**



PRODUCT PERFORMANCE DATA

Density	ASTM D3676	60 pcf
Hardness	ASTM D2240 (Shore A)	60 +/- 5
Tear Strength	ASTM D624	47 pli min
Elongation	ASTM D412	> 80%
Tensile Strength	ASTM D412	> 182 PSI
Resistance to Chemicals	ASTM F925	No Change
Coefficient of Friction	ASTM D2047	> 0.95
Static Load Limit	ASTM F970	0.005" @ 125 PSI
Force Reduction	ASTM F2772	23.60%
Energy Restitution	ASTM F2772	76.40%
Vertical Deformation	ASTM F2772	1.4mm
Flexibility	ASTM F137 1/4" Mandrel	Pass

PRODUCT DIMENSIONS

3/4" (18mm) x 48" x 25' Rolls



STRENGTH FROM WITHIN.

Scan QR code to view our catalog.

ORDER NOW

www.PMXSTRENGTH.com

**5310 Ashbrook Drive
Houston, TX 77081**

